

# Kanalreinigungsdüsen

## Kanalreinigungsdüsen 1/8"



	30.012SL10	30.012SL15	30.012SL27	30.012SL10F	30.012SL15F	30.012SL30F
1/8						
20 - 100						
min. l/min bei 100 bar	10	15	27	10	15	30
Schubstrahl	4 × Ø 0.80	4 × Ø 0.95	4 × Ø 1.20	4 × Ø 0.75	4 × Ø 0.90	4 × Ø 1.10
Frontstrahl	—	—	—	Ø 0.60	Ø 0.60	Ø 1.10
Strahlwinkel hinten	30°					
ØxL	16 × 18					
Gewicht [g]	12					
Recycling	—					

## Kanalreinigungsdüsen 1/4"



	30.0253SL10	30.0253SL15	30.0253SL30	30.0253SL10F	30.0253SL15F	30.0253SL30F
1/4						
30 - 110						
min. l/min bei 100 bar	10	15	30	10	15	30
Schubstrahl	3 × Ø 0.85	3 × Ø 1.10	3 × Ø 1.55	3 × Ø 0.80	3 × Ø 1.00	3 × Ø 1.50
Frontstrahl	—	—	—	Ø 0.60	Ø 0.80	Ø 0.80
Strahlwinkel hinten	30°					
ØxL	19 × 20					
Gewicht [g]	18					
Recycling	—					



	30.0256SL30	30.0256SL40	30.0256SL30F	30.0256SL40F	35.0253SL20	35.0253SL30
1/4						
30 - 110						
min. l/min bei 100 bar	30	40	30	40	20	30
Schubstrahl	6 × Ø 1.10	6 × Ø 1.20	6 × Ø 1.00	6 × Ø 1.20	3 × Ø 1.00	3 × Ø 1.40
Frontstrahl	—	—	Ø 0.80	Ø 0.80	4 × Ø 0.50	4 × Ø 0.50
Strahlwinkel hinten	30°					
ØxL	19 × 20					
Gewicht [g]	18					
Recycling	—					

	Anschlussgewinde ["]		Schubstrahl		Masse [mm]
	Anwendungsbereich [mm]		Frontstrahl		Gewicht [g]
	min. l/min bei 100 bar		Strahlwinkel hinten		Recycling

# Kanalreinigungsdüsen



**35.0256SL30    35.0256SL40**

	1/4	
	30 - 110	
	30	40
	6 × Ø 1.00	6 × Ø 1.10
	4 × Ø 0.50	4 × Ø 0.50
	30°	
	15°	
	19 × 20	
	18	
	—	

## Kanalreinigungsdüsen 3/8" - 3/4"



**30.038                    30.050                    35.050                    30.075                    35.075**











	3/8	1/2	1/2	3/4	3/4
	40 - 150	50 - 200	50 - 200	70 - 250	70 - 250
	10	50	50	50	50
	6 × M4	6 × M6	6 × M6	6 × M6	6 × M6
	1 × M4	1 × M6	3 × M4 1 × M6	1 × M6	4 × M6
	30°	30°	30°	30°	30°
	—	—	15°	—	15°
	25 × 37	30 × 47	30 × 47	38 × 60	38 × 60
	60	112	110	230	225
	x	x	x	x	x

	Anschlussgewinde ["]		Frontstrahl		Gewicht [g]
	Anwendungsbereich [mm]		Strahlwinkel hinten		Recycling
	min. l/min bei 100 bar		Strahlwinkel vorne		
	Schubstrahl		Masse [mm]		

# Kanalreinigungsdüsen

Kanalreinigungsdüsen 1" - 1 1/4"



	<b>30.100</b>	<b>35.100</b>	<b>30.100SP20</b>	<b>30.125</b>
	1	1		1 1/4
	150 - 350	150 - 350		200 - 400
	120	120		200
	8 × M8	8 × M8		8 × M8
	1 × M8	4 × M8		1 × M8
	30°	30°	20°	30°
	—	15°		—
	60 × 83	60 × 83		68 × 105
	750	750		1370
	x	x		x

	Anschlussgewinde ["]		Frontstrahl		Gewicht [g]
	Anwendungsbereich [mm]		Strahlwinkel hinten		Recycling
	min. l/min bei 100 bar		Strahlwinkel vorne		
	Schubstrahl		Masse [mm]		